




Arel D/I

The Arel D/I luminaire with a downlight and uplight feature is designed for offices and other public spaces. The luminaires are equipped with a matt anti-glare shield. Suspension mounting. The standard range includes two colour temperatures and sizes. Integrated LED. Suspension fixtures included.

- Steel housing, matt aluminium anti-glare shield.
- White, RAL 9003.
- Protection class I.
- Linkable, two 3 x 2,5 mm² spring terminal blocks, in Dali-models two 5 x 2,5 mm² spring terminal blocks. The up- and downlights have their own spring terminals.
- Installation height 2–4 m.
- Integrated LED 54–79 W, 5,800–8,800 lm.
- Colour temperatures 3,000 K and 4,000 K. CRI > 80 / Ra 80.
- MacAdam 3 SDCM.
- IP20.
- The standard range includes on/off and Dali models.
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L70 100,000 h (Ta25°C).
- Rated lifetime L80 80,000 h (Ta25°C).
- Power source service life 50,000 h.
- WH = white, DA = Dali, AL = aluminium, MA = matt.
- Also available: Casambi, ActiveAhead, Philips SR, 1–10 V and Switch Dim solutions. CRI > 90 / Ra > 90 available by special order. Also available with various connecting cable solutions and a pull switch (on/off and Dali). High gloss anti-glare shield, luminous flux packages 2700–8800 lm and gray color, RAL 9007, also available on request.



By order

Arel D/I on/off

NO.	CODE		W	LM
4222726	D2ARJA	1245x245 IP20 54W/830 AL MA WH	54	5800
4222727	D2ARJB	1245x245 IP20 54W/840 AL MA WH	54	5800
4222728	D2ARKC	1545x245 IP20 79W/830 AL MA WH	79	8800
4222729	D2ARKD	1545x245 IP20 79W/840 AL MA WH	79	8800

Arel D/I Dali

NO.	CODE		W	LM
	D2ARJA-DALI	1245x245 IP20 54W/830 DA AL MA WH	54	5800
	D2ARJB-DALI	1245x245 IP20 54W/840 DA AL MA WH	54	5800
	D2ARKC-DALI	1545x245 IP20 79W/830 DA AL MA WH	79	8800
	D2ARKD-DALI	1545x245 IP20 79W/840 DA AL MA WH	79	8800