



Boulevard




Boulevard is a stylish and adaptable luminaire that is suitable for use in parks, squares, footpaths and yard areas. Made of high-quality materials, the luminaire is of European quality and it provides even illumination. Aluminium housing and hardened glass diffuser. The luminaire's impact resistance class is high. It is mounted directly onto a pole.

- Die-cast aluminium housing. Hardened glass diffuser
- Black, RAL9005.
- Protection class I.
- Pole mounting 60 mm.
- Not linkable, -o 3 x 1,0 mm², cable 6 m.
- Wind surface area 0.157 m², top / 0.012 m², sides.
- Installation height 4–6 m.
- Colour temperature 4,000 K. CRI > 70 / Ra > 70.
- MacAdam 5 SDCM.
- IP66.
- IK09.
- Integrated LED 40 W 4200 lm
- On/off.
- 6kV surge protection.
- Ambient temperature range -40 ... 35 °C.
- Rated lifetime L90 100,000 h (Ta25°C).
- Power source service life 100,000 h (Ta25°C).
- GLC = Clear flat glass, Asym = asymmetrical light distribution, BK = black
- Power and luminous flux version 60W 6300 lm is also available on a project-specific basis. Color temperature 3000 K. Models with a narrow light distribution, Dali-2 control and night-time dimming are available by special order. Cables of various lengths and types are available by special order.

By order

Boulevard

NR.	CODE	W	LM
4546514	A5BULA IP66 IK09 40W/740 GLC BK	40	4200
4546515	A5BULB IP66 IK09 40W/740 ASYM GLC BK	40	4200



Asym.