







## Compact Outdoor

Compact Outdoor is an adjustable downlight range, with full IP65 classification. The luminaires are particularly well suited for use in wet spaces and on exterior surfaces, eaves and open shuttering, as well as terrace roof structures. Colour temperatures: 3,000 K and 4,000 K. The luminaire is dimmable.

- Aluminium housing and acrylic diffuser.
- White powder-coated, RAL9010. Black powder-coated, RAL9005.
- Protection class II.
- Recessed mounting on a ceiling.
- Connecting wire 2 x 0.75 mm<sup>2</sup>. Connection in a separate box.
- Installation height 2–4 m.
- Adjustable, can be turned +/-15 degrees.
- Colour temperatures 3,000 K and 4,000 K. CRI > 80 / Ra > 80.
- MacAdam 3 SDCM.
- IP65/IP65.
- IK03.
- Integrated LED 5W / 500 lm.
- Dimming: rising- and trailing-edge control.
- Ambient temperature range -20 ... 25 °C.
- Rated lifetime L70 50,000 h
- Power source service life 50,000 h.



• In stock

### Compact Outdoor

NO.	CODE		W	LM
• 4146547	A1COMA	Tilt IP65 5W/840 36D DIM ACC W	5	500
• 4146548	A1COMB	Tilt IP65 5W/830 36D DIM ACC W	5	500
• 4146549	A1COMC	Tilt IP65 5W/840 36D DIM ACC B	5	500
• 4146550	A1COMD	Tilt IP65 5W/830 36D DIM ACC B	5	500

