








Fresa

The Fresa IP65 luminaires make an excellent lighting solution for industrial facilities, multi-storey car parks, garages and shelters. They are made of high-quality polycarbonate, while the latches are made of stainless steel. The luminaires can be mounted on the ceiling or the wall. You can also mount the luminaire suspended with the accessories included in the delivery. The range is available in two lengths. Both lengths are available with 5 and 10 metre connecting cables, making them suitable for use on worksites.



- Polycarbonate body and diffuser.
- Grey.
- Protection class I.
- Surface or suspension mounting.
- Linkable 5 x 2.5 mm².
- Connecting cable models: 5 m, 3 x 1.5 mm² rubber cable, schuko plug. 10 m, through-wired, 3 x 1.5 mm² rubber cable. A schuko plug at one end (9 m), a schuko socket at the other end (0.5 m).
- Installation height 2–5 m.
- Colour temperature 4,000 K. CRI > 80 / Ra > 80.
- IP65.
- IK08.
- Fixed LED 1,200 mm 41 W / 4,800 lm; 1,500 mm 56 W / 6,000 lm.
- MacAdam 5 SDCM.
- On/Off and models with a connecting cable.
- Ambient temperature range -25 ... 35 °C.
- Rated lifetime L70 50,000 h (Ta35°C).
- Project-specific connecting wires, Dali and Casambi solutions available on request.



By order, • In stock

Fresa on/off

NO.	CODE	W	LM
• 4310604	A3TEJA IP65 41W/840 PCO GR	41	4800
• 4310605	A3TEJB IP65 56W/840 PCO GR	56	6000

Fresa Dali

NO.	CODE	W	LM
	A3TEJA-DALI IP65 41W/840 DA2 PCO GR	41	4800
	A3TEJB-DALI IP65 56W/840 DA2 PCO GR	56	6000

Fresa Casambi

NO.	CODE	W	LM
	A3TEJA-CA IP65 41W/840 CA PCO GR	41	4800
	A3TEJB-CA IP65 56W/840 CA PCO GR	56	6000

Fresa with cable

NO.	CODE	W	LM
4310510	A3TEIS IP65 41W/840 PCO GR 5M	41	4800
4310511	A3TEIT IP65 56W/840 PCO GR 5M	56	6000
4310512	A3TEIU IP65 41W/840 PCO GR 10M	41	4800
4310513	A3TEIV IP65 56W/840 PCO GR 10M	56	6000

