











Handy

Our popular worktop luminaire range Airam Handy is designed for illuminating work areas in kitchens and utility rooms. Before mounting, the LED lamp's colour temperature is selected via a mechanism within the luminaire frame. The options are 3,000 K (pure white) and 4,000 K (bright white). The luminaire is available with four length and four power options. Handy luminaires can be mounted flush against the surface or at an $% \left(1\right) =\left(1\right) \left(1\right)$ angle of 45°. Read more about our Handy luminaires with an earthed double socket and an on/off switch for luminaire-specific control of lighting.

- · Aluminium body and polycarbonate diffuser.
- · Protection class I.
- Surface mounting, linkable, 4 x 2.5 mm² (luminaires with sockets) or 3 x 2.5 mmm² (luminaires without sockets).
- · Power, luminous flux, and length options:

LED 5 W, 500 lm / 450 mm LED 8 W, 800 lm / 550 mm LED 11 W, 1,200 lm / 750 mm LED 14 W, 1,500 lm / 1,100 mm

- The LED lamp's colour temperature (3,000 K or 4,000 K) is selected before installation. CRI > 80 / Ra > 80.
- The handedness of the socket can be changed, making the luminaire suitable for left- and right-handed installation.
- · Enclosure class IP21.
- · Ambient temperature range of 5 to 25 °C.
- · Rated lifetime L70B50 60,000 h.
- · Protective cover against dripping available as accessory.
- DSO = Double shuko power socket.

In stock

Handy with socket

	,						
	NO.	CODE		W	LM		
•	4107100	A1TRBM	450 IP21 5W 830/840 DSO WH	5	500		
•	4107101	A1TRBN	550 IP21 8W 830/840 DSO WH	8	800		
•	4107103	A1TRBO	750 IP21 11W 830/840 DSO WH	11	1200		
	4107112	A1TRBP	1100 IP21 14W 830/840 DSO WH	14	1500		

Handy without socket


	NO.	CODE		W	LM
•	4126293	A1TRBI	450 IP21 5W 830/840 WH	5	500
•	4126294	A1TRBJ	550 IP21 8W 830/840 WH	8	800
•	4126295	A1TRBK	750 IP21 11W 830/840 WH	11	1200
	/126296	Δ1TPRI	1100 IP21 14W 830/840 WH	1/1	1500


Handy Accessories

	NO.	CODE	
•		A1HATS	450 protec. against dripping
•		A1HATT	550 protec. against dripping
•		A1HATQ	750 protec. against dripping
•		A1HATP	1100 protec. against dripping




Handy with the socket









Handy without the socket



