






Highbay

This energy-efficient Highbay lighting fixture is designed for illuminating high spaces. Typical applications include warehouses, lobbies and other premises with high ceilings. The luminaire is available in three output options and as Dali-2 and wireless control models. Its energy-efficiency is up to 140 lm/W. The Dali-2 models can be customised for wireless control. A mounting fixture is available as an accessory.

- Pressure-cast aluminium body and UV-protected, impact-resistant polycarbonate diffuser.
- Black, RAL 9017.
- Protection class I.
- Mounting on a suspension rail and a ceiling or suspended with a chain or wire.
- Installation height 5–12 m.
- Dali-2-versions linkable 5 x 2,5 mm².
- Casambi-versions linkable 3 x 2,5 mm².
- Colour temperature 4,000 K. CRI > 80 / Ra > 80.
- IP65.
- IK10.
- Fixed LED 90 W / 12,600 lm, 150 W / 21,000 lm, 240 W / 36,000 lm.
- MacAdam 5 SDCM.
- Dali-2- and Casambi-models 90 W, 150 W and 240 W.
- Dali-2- and Casambi-models are equipped with a fixed connection box.
- Ambient temperature range -30 ... 50 °C.
- Rated lifetime L70 100,000 h (Ta35°C).
- Rated lifetime L90 35 000 h.
- Power source rated lifetime 100,000 h.
- Available also as ActiveAhead versions. Also available with various connecting wire solutions.



Mounting on a suspension rail and a ceiling or suspended with a chain or wire.

By order, • In stock

Highbay Dali

NO.	CODE	W	LM
• 4310658	A3SYCH IP65 90W/840 WB DA2 PCC	90	12600
• 4310659	A3SYCF IP65 150W/840 WB DA2 PCC	150	21000
• 4310657	A3SYCD IP65 240W/840 WB DA2 PCC	240	36000

Highbay Casambi

NO.	CODE	W	LM
A3SYCI	A3SYCI IP65 90W/840 WB DA2 CA PCC	90	12600
A3SYCG	A3SYCG IP65 150W/840 WB DA2 CA PCC	150	21000
A3SYCE	A3SYCE IP65 240W/840 WB DA2 CA PCC	240	36000