





Kappa

With its rounded corners, this elegant luminaire designed for both indoor and outdoor use blends in with décor in both new and renovated buildings. All the models are available with an integrated LED and in two different colour temperatures. The range is also available with an E27 base. Light sources only available via separate order. High-quality surface treatment.

- Aluminium housing and frosted glass diffuser.
- Anthracite, silver, black and white.
- Protection class I.
- Not linkable, 3 x 2.5 mm²
- Installation height 0.5–4 m.
- Integrated LED 9W / 830 710lm, 840 740 lm.
- Led lamp max. 11 W A60 E27, not included.
- Lamp recommendations: Airam Frost led -range.
- Colour temperatures of the integrated LEDs 3,000 K and 4,000 K. CRI > 80 / Ra > 80.
- IP55.
- IK03.
- On/off.
- Ambient temperature range -25 ... 25 °C
- Rated lifetime L70 50,000 h (Ta25°C).
- Power source service life 50,000 h.
- AN = anthracite, SI = silver, BK = black, WH = white.



By order

Kappa 830

NO.	CODE	W	LM
4507452	B5KAAD IP55 IK03 9W/830 GLFR ANT	9	710
4507451	B5KAAC IP55 IK03 9W/830 GLFR SI	9	710
4507450	B5KAAB IP55 IK03 9W/830 GLFR BK	9	710
4507449	B5KAAA IP55 IK03 9W/830 GLFR WH	9	710

Kappa 840

NO.	CODE	W	LM
4509966	B5KAAJ IP55 IK03 9W/840 GLFR ANT	9	740
4509965	B5KAAH IP55 IK03 9W/840 GLFR SI	9	740
4509964	B5KAAG IP55 IK03 9W/840 GLFR BK	9	740
4509963	B5KAAF IP55 IK03 9W/840 GLFR WH	9	740

Kappa E27

NO.	CODE
4509984	B5KAAN IP55 IK03 E27 GLFR ANT
4509969	B5KAAM IP55 IK03 E27 GLFR SI
4509968	B5KAAL IP55 IK03 E27 GLFR BK
4509967	B5KAAK IP55 IK03 E27 GLFR WH