

IP54

-O-
5 x 2,5



DALI



Keto Pro

Keto Pro is a versatile general luminaire with IP54 protection, designed for use in warehouses, corridors and wet indoor spaces. The luminaire has a steel housing and a low, narrow structure, and it is available with four different outputs, as well as two housing lengths and colour temperatures. The Keto Pro range also includes radar and Dali models. With the protection grid, available as an accessory, the luminaire is suitable for installation in sports halls and facilities.

- Steel housing and opal acrylic diffuser (ACO).
- White RAL 9016.
- Protection class I.
- Mounting on a ceiling.
- Linkable 5 x 2,5 mm².
- Installation height 2–6 m
- Colour temperatures: 3,000 K and 4,000K. CRI > 80 / Ra > 80.
- IP54.
- Fixed LED: 1210 mm: 18 W / 2600 lm; 25 W / 3800 lm; 36 W / 5400 lm. 1500 mm: 47 W / 6900 lm.
- MacAdam 3 SDCM.
- On/off, Dali and RA/MS model (25 W / 36 W).
- RA/MS- and PIR/MS-models maximum of three slave luminaires.
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L70 100 000 h (Ta25°C).
- Rated lifetime L80 80 000 h (Ta25°C).
- RA/MS = radar models with master/slave connection, DA = Dali, PIR/MS = infrared models with master/slave connection.
- Also available as Casambi and 1–10V models on a project-specific basis. CRI > 90 available by special order. The colour temperature options available are: 2,700 K, 5,700 K and 6,500 K as well as Tunable White. The lengths 630 mm: 20 W / 2500 lm and 34 W / 4200 lm. 1500 mm: 58 W / 8200 lm also available. A protection grid and suspension set available by special order.



By order, • In stock

Keto Pro

NO.	CODE		W	LM
4310633	D3KEKA	IP44 18W/830 ACO WH	18	2600
4310634	D3KEKB	IP44 18W/840 ACO WH	18	2600
• 4338520	D3KEKC	IP54 25W/840 ACO WH	25	3800
4310635	D3KEKE	IP44 36W/830 ACO WH	36	5400
• 4310636	D3KEKF	IP44 36W/840 ACO WH	36	5400
4310637	D3KEKJ	IP44 47W/830 ACO WH	47	6900
4310638	D3KEKK	IP44 47W/840 ACO WH	47	6900

Keto Pro Dali

NO.	CODE		W	LM
	D3KEKA-DALI	IP44 18W/830 DA ACO WH	18	2600
	D3KEKB-DALI	IP44 18W/840 DA ACO WH	18	2600
	D3KEKE-DALI	IP44 36W/830 DA ACO WH	36	5400
	D3KEKF-DALI	IP44 36W/840 DA ACO WH	36	5400
	D3KEKJ-DALI	IP44 47W/830 DA ACO WH	47	6900
	D3KEKK-DALI	IP44 47W/840 DA ACO WH	47	6900

Keto Pro sensor luminaires

NO.	CODE		W	LM
• 4338521	D3KEKI	IP54 25W/840 RA/MS ACO WH	25	3800
4338503	D3KEKH	IP54 36W/830 RA/MS ACO WH	36	5400
• 4338519	D3KEKG	IP44 36W/840 RA/MS ACO WH	36	5400
• 4338567	D3KEKL	IP54 25W/840 PIR/MS ACO WH	25	3800
• 4338568	D3KEKM	IP54 36W/840 PIR/MS ACO WH	36	5400