





Lid Mini

A wall-mounted, low-profile luminaire for indoor and outdoor use. Glass diffuser's impact resistance: IK10. Thanks to its elegant design, the Lid luminaire offers an excellent lighting solution for modern spaces and loft apartments. The luminaire comes with an integrated LED, available in two colour temperatures. The luminaire housing is coated with polyester paint that is resistant to corrosion and UV radiation. The screws are made of stainless steel.



- Aluminium housing and opal glass diffuser.
- Anthracite, silver, black and white.
- Protection class I.
- Surface mounting.
- Not linkable, 3 x 1.5 mm².
- Installation height 0–3 m.
- Integrated LED 5W, 135–145 lm.
- Colour temperatures 3,000 K and 4,000 K. CRI > 80 / Ra > 80.
- IP65.
- IK10.
- On/off.
- Ambient temperature range -25 ... 35 °C
- Rated lifetime L70 50,000 h (Ta25°C).
- Power source service life 50,000 h.
- AN = anthracite, SI = silver, BK = black, WH = white.
- Also available in Corten colour on a project-specific basis.



By order

Lid Mini 830

NO.	CODE	W	LM
4512340	B5LDAD LID MINI 5W/830 AN	5	135
4512341	B5LDAC LID MINI 5W/830 SI	5	135
4512342	B5LDAB LID MINI 5W/830 BK	5	135
4512343	B5LDAA LID MINI 5W/830 WH	5	135

Lid Mini 840

NO.	CODE	W	LM
4512345	B5LDAJ LID MINI 5W/840 AN	5	145
4512346	B5LDAH LID MINI 5W/840 SI	5	145
4512347	B5LDAG LID MINI 5W/840 BK	5	145
4512348	B5LDAF LID MINI 5W/840 WH	5	145