






Multibay

Multibay is a cost-efficient high-bay luminaire that combines versatility and excellent value for money. Efficacy can be adjusted on the luminaire. Luminaire is made of durable aluminum which is suitable for almost any location that requires high light output, such as high, open hall and storage spaces. The luminaire comes with a ready carabiner hook, which allows an easy and quick suspension installation. Surface mounting is possible with a separately ordered mounting bracket. The on/off version has three power options. The Dali version can be configured to the desired power during configuration.

- Aluminium body, polycarbonate lenses, opening angle 90 degrees.
- Black, RAL 9017.
- Protection class I.
- Not linkable 3 x 1 mm² (on/off) ja 5 x 1 mm² (1-10V), use separate junction box.
- Cable length 300 mm.
- Suspension or surface mounting with an installation bracket (4338604), available by separate order.
- Installation height 6–10 m.
- Colour temperature 4000 K. CRI > 80 / Ra > 80.
- IP65.
- IK08.
- Integrated LED, efficacy can be adjusted on the luminaire:
- On/off: 110 W / 16 500 lm; 150 W / 22 000 lm; 200 W / 28 000 lm.
- Dali: 200 W / 28 000 lm.
- MacAdam 5 SDCM.
- On/off and Dali.
- Ambient temperature range -30 ... 45 °C.
- Rated lifetime L70 > 100 000 h (Ta25°C).
- Rated lifetime L80 80 000 h (Ta25°C).
- Rated lifetime L90 40 000 h (Ta25°C).



• In stock

Multibay

NO.	CODE	W	LM
• 4338602	A3SYAA IP65 IK08 200W 28000lm 840 90D	200	28000
• 4338603	A3SYAB IP65 IK08 200W 28000lm 840 90D DA2	200	28000

Multibay ceiling bracket

NO.	CODE
• 4338604	A3SYAC Ceiling bracket Multibay



High bay luminaire with efficacy change

A cost-effective choice for almost any high space. The efficacy can be adjusted on the luminaire.