





Rigel 230V

The Rigel 230V LED strip is designed for interior and exterior spaces where long, continuous lines of light are required. The strip's maximum length is 50 metres. It is connected directly to a 230 V mains network. Suitable applications include offices, public spaces and hotels. Because of its IP65 rating, the strip can also be used for exterior surfaces and wet spaces. The strips are available in two colour temperatures. Rigel is delivered as 50 m reels or cut to measure.

- UV-protected, PVC-coated LED strip.
- Length 50 m.
- 1.5 input cable with a schuko plug.
- Surface mounting on the Rigel profile or with separate fittings.
- Colour temperatures 3,000 K and 4,000, K.
CRI > 80 / Ra > 80.
- IP65.
- IK08.
- 7 W/m / 400 lm/m.
- Can be cut to measure at increments of one metre (1–50 m).
- Ambient temperature range -25 ... 25 °C.
- Rated life time L70 50,000 h (Ta25°C).



Mounting profile for 4222779 Rigel led strips. Length 2000 mm. Ensures a straight installation, and secures the strip to the installation surface. The profile has fastening holes for 3,5 x 20 countersunk screws every 180 mm, a total 12 holes.

• In stock

Rigel 230V

NO.	CODE	W	LM
• 4209541	A2RICA	IP65 7W/m 830 50m	350 20000
• 4209542	A2RICD	IP65 7W/m 840 50m	350 20000

Rigel 230V lisätarvikkeet

NO.	CODE	
• 4209552	A2RIEA	Power cord 1.5m
• 4209554	A2RIEC	Bracket 10pce
• 4209556	A2RIEE	Double side connector

4209552



4209554



4209556

