



Spot-On P

The suspension-mounted Spot-On P range with adjustable colour temperature offers an ideal lighting solution for cafés, restaurants, and small shop properties. Equipped with a dimming feature, this spotlight provides numerous options for illuminating your space. By selecting a suitable colour temperature and brightness, you can create an intimate, tranquil atmosphere and highlight specific features of the space. In addition to the Spot-On P luminaires, you can use Spot-On spotlights to create a suitable lighting solution. Utilising both spotlights and suspension-mounted luminaires lets you form eye-catching lighting groups that are easy to adjust. Our luminaires provide excellent colour-rendering properties and are made from high-quality materials. The product's colour options are black and white, and you can choose either a model with a switch for dimming and adjusting the colour temperature or one in which the colour temperature automatically grows warmer upon dimming.

- Housing is made of injection-moulded aluminium. Acrylic diffuser. Bevelled aluminium reflector, 36°.
- White, RAL9010 and black, RAL9005.
- Protection class I.
- Mounting on a three-phase-contact rail.
- Compatible three-phase-contact rails: Global Pro (formerly Nokia); XTS, XTTS, and XTSC three-circuit tracks; and Erco, iGuzzini, Unipro T3, and Eutrac tracks.
- Surface mounting possible with adapter 1452093 and 1453093, to be ordered separately.
- Installation height 3–5 m
- The total height of the luminaire is 2 metres downwards from the installation surface.
- Colour temperatures: 3000 K and 4000 K, changeable from the luminaire. The colour temperature of the DTW models changes from 3000 K to 1800 K with dimming. CRI > 90 / Ra > 90.
- IP20.
- IK02.
- Integrated LED 13 W, 900 lm.
- MacAdam 3 SDCM.
- Dimmable.
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L70 100 000 (Ta25°C).
- Rated lifetime L80 65 000 (Ta25°C).
- Comes with a honeycomb anti-glare screen and two optional reflectors for narrower light beam (12D and 24D).

• In stock

Spot-On P

| NO. | CODE | W | LM |
|-----------|--------------------------------------|----|-----|
| • 4146593 | A1SPOC IP20 13W 930/940 36D DIM BK P | 13 | 900 |
| • 4146594 | A1SPOD IP20 13W 930/940 36D DIM WH P | 13 | 900 |
| • 4146693 | A1SPOG IP20 14W 918-930 36D DTW BK P | 14 | 900 |
| • 4146694 | A1SPOH IP20 14W 918-930 36D DTW WH P | 14 | 900 |

