




Tri-Proof

The through-wired Tri-Proof IP65 industrial luminaire can be mounted on a wall or a ceiling. Its couplers can be pulled out from the luminaire ends, making installation extremely quick and easy. Typical applications include industrial and parking facilities and garages. Equipped with connecting wires, the luminaire is also suitable for use on worksites.

- Polycarbonate body and diffuser.
- White.
- Protection class II.
- Mounting on a ceiling and wall.
- Linkable 3 x 2.5 mm².
- Installation height 2–6 m.
- Colour temperature 4,000 K. CRI > 80 / Ra > 80.
- IP65.
- IK08.
- Fixed LED 18 W / 1,900 lm, 36 W / 3,700 lm, 54 W / 5,600 lm.
- MacAdam 5 SDCM.
- On/Off.
- Ambient temperature range 0 ... 25 °C.
- Rated lifetime L70 50,000 h (Ta25°C).
- Project-specific connecting wires available, for example, for worksite use.



• In stock

Tri-Proof

NO.	CODE		W	LM
• 4310606	A3TUEA	600 IP65 18W/840 PCO WH	18	1900
• 4310607	A3TUEB	1200 IP65 36W/840 PCO WH	36	3700
• 4310608	A3TUEC	1500 IP65 54W/840 PCO WH	54	5600